













## COMPACT, COMPLIANT, COST-EFFECTIVE SCREENING AUDIOMETER.

### Technical Specifications

-  Air Conduction: 250 Hz–8 kHz (-20 to 120 dB),
-  Noise Options: Wide and Narrow band
-  Masking Attenuator: 0–100 dB, in 5 dB steps
-  THD + Noise: <1% at 100 dB intensity
-  Input Power: 110V–250V AC, 50/60 Hz
-  Operating Range: 10–40 °C, 5–90% humidity
-  Storage Range: -10–60 °C, 5–90% humidity
-  Dimensions: 19 × 13.5 × 6 cm
-  Weight: 4.0 kg (including audiometer & accessories)
-  Carry Case: 42 × 35 × 13 cm, polyester with plastic handle

### Key Features

- Touch Sensitive Keys
- Click-less operation
- Precision Output – Accurate frequency & threshold generation
- Special Tests – Warble Tone
- Output Modes – Air (L/R)
- +10 dB Key & Dedicated Pulse Tone Key
- Masking – Wide & Narrow Band Noise with L-R Toggle

### CONTACT

Unit No 220/221, Hema Industrial Estate, Rajmata Jijabai Marg, Sarvodaya Nagar, Jogeshwari East, Mumbai, Maharashtra 400060.

WhatsApp: 7977310515

Call: 9870411396

Email: [adityasolutions.mdsales@gmail.com](mailto:adityasolutions.mdsales@gmail.com)